

*Anticipating the worst drives us to develop the **very best.***

For more than 40 years, CSE Corporation has anticipated the worst emergencies and environments. This experience and our dedication to safety technology has led to the introduction of the SRLD — a revolutionary Self-Contained Self-Rescuer (SCSR). Our innovative *QuickStart Technology* provides up to 40% faster oxygen generation in the first minutes, supplying more oxygen when it's needed the most. The state-of-the-art SRLD is the smallest and lightest, most advanced one-hour belt-wearable SCSR available today.

Our long standing commitment to safety and technology helps us produce the very best product for you when you need it the most.

SRLD

Self-Rescuer Long Duration

Advanced One-Hour Performance
featuring *QuickStart Technology*



csecorporation.com



SRLD

Self-Rescuer Long Duration

Advanced One-Hour Performance
featuring QuickStart Technology

The SRLD is designed in response to today's most critical market requirements.

Complete with enhanced safety, reliability and increased performance.

The SRLD is the smallest 60 minute belt-wearable SCSR available today.

FEATURES & BENEFITS

- Rated duration 60 minutes
- Faster oxygen generation at the start of deployment.
- Advanced starter oxygen delivery system
- Easy to follow user instructions on-board
- Enhanced manual start
- Robust for a difficult environment
- Complete inspection tools available
- Advanced training program including a suite of 3 expectation training devices available
- 5-year carried service life
- 10-year permanent storage service life
- Easy to inspect

Note: Actual duration depends on the work rate and size of the individual.



csecorporation.com

600 Seco Road | Monroeville, PA 15146
Ph: (800) 245-2224 | Fx: (412) 856-9203

TECHNICAL SPECIFICATIONS

Operating performance

| | |
|-------------------------|------------|
| Usage period | |
| Ve Volume 10 Liters/min | 3.5 hours |
| Ve Volume 30 Liters/min | 75 minutes |
| VO2 1.35 Liter O2/min | 60 minutes |

Environmental Conditions

| | |
|-----------------------|-----------------|
| Storage temperature | -20°F to 150°F |
| Operating temperature | 32°F to 150°F |
| Relative humidity | up to 100% |
| Barometric pressure | 700 to 1300 hPa |

Breathing bag volume > 3 liters

Breathing resistance

| | |
|----------------------------|------------|
| Inhalation plus exhalation | |
| @ 30 L/min at deployment | 70 mm H2O |
| @ 30 L/min at 60 minutes | 150 mm H2O |

Physical dimensions

| | |
|----------------------|-----------------------|
| Dimensions H x W x D | 8.5 x 6 x 4.25 inches |
| Weight (carried) | 5 lb 14 oz |
| Weight (deployed) | 5 lb 1 oz |

Approval NIOSH/MSHA TC-13F-0645

